

# 2360-EXTEND

## SELECTABLE GALLONAGE FOAM NOZZLE



**Style 2360E**

- Lightweight hardcoat anodized aluminium construction
- Designed for water and foam applications with Class A and AFFF foam in a single dynamic nozzle with retractable foam aspiration sleeve
- Combination pattern nozzle with versatile multiple flow settings
- Suitable for use with eductors, on-board foam proportioning systems, and can efficiently transform from aspirated foam to wide protective fog pattern
- Produces straight stream for maximum reach and superb wide fog pattern for optimum fire fighter protection with the ability to instantly aspirate foam by sliding inbuilt sleeve forward
- No foam aeration tubes required for aspirating foam, comes with stainless steel spinning teeth for superior fog pattern
- Available in tip only configuration and shutoff combinations
- Dynamic nozzle with retractable foam aspiration sleeve
- Stainless filter mesh prevents blockage caused by debris
- Minimal maintenance reflected in robust design, precision machining and quality materials

### Specification

Style	Inlet Size	Length	Weight Lbs(kg)	Flow Settings
				LPM
2360E	1" (25mm)	8.5"-8.8" (215 mm-223 mm)	3.1 (1.4kg)	20-40-100-150 LPM

# 2360-EXTEND

## SELECTABLE GALLONAGE FOAM NOZZLE



Flush without changing pattern or shutting down

Laser-etched anodized label for excellent durability and visibility

Unique serial number etched for easy identification

New and improved handle design

Large metal flow selection ring for enhanced grip

Reinforced metal pieces improve durability

Baffle etched with pressure (psi and bar)

Stainless filter mesh prevents blockage caused by debris

Choice of 1" or 1-1/2" swivel inlet

Stainless steel spinning teeth

Heavy-duty chrome plated metal shutoff ball for smooth action and long life

Ergonomic design pistol grip (available in various colours)

**Style 2360E**



- When the outer sleeve is in the retracted position, the nozzle operates in the same way as the Style 2360 with four flow settings and flush mode
- To activate aspirating function, slide the outer sleeve forward and adjust to narrow fog or stream pattern in order to control reach and aspiration
- If immediate wide fog pattern is required, the sleeve can be retracted instantly to its water discharge position